

Yealink T26P Product Sheet



The Yealink SIP-T26P is an advanced IP phone designed for maximum functionality and efficiency in the everyday business environment. Equipped with the TI TITAN chipset, it offers high-definition voice quality through a TI voice engine, HD handset, HD speaker and HD codec (G.722). Ten DSS keys are built in to programme IP-PBX features, such as BLF/BLA, intercom, call pick-up, XML browser and hot desking. Six navigation keys and four soft keys make it very easy to use the phone. Ten dedicated further keys give you direct access to audio and call control functions. In addition, the SIP-T26P includes rich external interfaces, such as 2xLAN, PoE, headset and expansion module ports, 802.1x support and Open VPN security standards.

FEATURES

- ✓ TI TITAN chipset and TI voice engine
- ✓ 132x64 graphic LCD
- ✓ 3 VoIP accounts, Broadsoft /Avaya/Asterisk validated
- ✓ HD Voice: HD Codec, HD Handset, HD Speaker
- ✓ 45 keys including 13 programmable keys
- ✓ BLF/BLA, SMS, Voicemail, Intercom
- ✓ Localized language, XML phonebook
- ✓ FTP/TFTP/HTTP, PnP Auto-provision
- ✓ SRTP/HTTPS/TLS, VLAN, QoS
- ✓ PoE, Headset, 2xRJ45, Expansion module
- ✓ SIP application: support call forward/ transfer (blind/attended)/ holding/ waiting/ 3 way talking/ conference/ paging and intercom/ call park/call pickup/ join call/ redial and unredial/ click to dial/ secondary dialing automatically
- ✓ Incoming calls /outgoing calls / missed
- ✓ 1xRJ9 handset port
- ✓ 1xRJ9 headset port
- ✓ 2xRJ45 10/100M Ethernet ports
- ✓ Power over Ethernet (IEEE 802.3af)

Maintenance and Management

- ✓ FTP/TFTP/HTTP/PnP auto-provision
- ✓ Configuration: browser/phone/auto-provision
- ✓ Direct IP call without SIP proxy
- ✓ Dial number via SIP server
- ✓ Dial URL via SIP server
- ✓ Transport Layer Security (TLS)
- ✓ Digest authentication using MD5/MD5-sess
- ✓ Secure configuration file via AES encryption
- ✓ Phone lock for personal privacy protection
- ✓ Admin/user configuration mode



Dominic Sardinha
083 628 1427

Abacus
telecomm